

LBR-B SmartFilter

LBR-B SmartFilter with discharge bins for light dust applications

LBR-B SmartFilter



The LBR-B is an advanced, IIoT ready, reverse air baghouse suited for continuous duty applications with low air volumes and light loading. The modular filter housing can be scaled based on the required airflow and modules can be field added if additional capacity is required.

Air enters the filter through an inlet module or hopper inlet where the heavy / large dust particles drop out of airstream. The remaining fine particles pass through an array of highly efficient SUPERBAG filters allowing clean air to pass through. As dust accumulates on the filter bags, a regeneration fan located on each filter module blows air in the reverse direction dislodging the collected dust into the hopper where it is collected into the dust bins located below the hopper.

The LBR SmartFilter features the Insight Control Panel offering complete control of the filter and system accessories. Sensors located throughout the system monitor and collect critical operational data for the local controls and can be connected to the Nederman cloud based IIoT platform for remote monitoring and system data analytics.

- **Configurable.** Modular design combined with a wide range of filter and system accessories allows the LBR SmartFilter to be configured to your factory's unique needs. A variety of filter sizes, depths and ability to handle either overpressure (positive) or vacuum (negative) airflow arrangement means the filter is optimized for your needs.
- **Future Proof.** The LBR SmartFilter controls are IIoT ready as standard, and our proprietary Insight platform enhances their current operation and prepares their factory for a digital future. Filter modules can be added in field if additional capacity is required.
- **Low Operational Cost.** 5-7 years of filter life, low operational pressure losses and efficient filter cleaning reduces the total cost of ownership compared to pulse jet or mechanical shaker alternatives.
- **Regulatory Compliance.** The LBR SmartFilter complies with the latest ATEX and NFPA combustible dust standards and regulations and our trained, experienced sales teams can provide a complete, turn-key compliant system.
- **Sustainability.** The LBR SmartFilter offers an energy efficient solution capable of recovering waste material to be reused or recycled.

Product name	LBR-B SmartFilter
Installation	Outdoor
Material	Housing in galvanised sheet steel
Suitable for combustible dust	True

LBR-B SmartFilter

Filter cleaning method	Reverse air pulse
Application	Dust
Working pressure (kPa)	5
Filter Area (m ²)	Per module HJ: 85 Per module HE: 42 Per module LJ: 40 Per module LE:20
Operating Temperature	-20 to 75°C
Power Voltage (V)	208-600
Filter type	Bag
Filter material	Superbag 2000 XT15 with ø200 mm collar
Power (kW)	Regeneration fan - 1,1 kW (option 2,2 kW)
Note	Configurable product




LBR-B SmartFilter

Model
LBR-B*

**Configurable product*

LBR-B SmartFilter



Unit	Type	A #	B	D***	F	G	H	I	J**	K**	M	O	P**
mm	J	2400	1106	485	1200	800	3600	720	3420	4220	2321	1260	2960
in	J	94.5	45.67	19.09	47.24	31.50	141.73	28.35	134.65	166.14	91.38	49.61	116.54
Unit	Type	Q	R	S	U	W	X						
mm	J	135	2400	115	150	47	23						
in	J	5.31	94.5	4.53	5.91	1.85	0.91						

* Optional position of outlet / reg. fan.

Filter length		
Type	H1	
	mm	in
1 HJ	1200	47.24
2 HJ	2400	94.5
3 HJ	3600	141.73
4 HJ	4800	189.0

L1 - telescopic filter legs				
Type	Min. Adjust		Max. Adjust	
	mm	in	mm	in
L= 1196	155	6.1	850	33.46
L= 1596	555	21.85	1250	84.65
L= 2195	1155	45.47	1850	72.83
L=2596	1555	61.22	2250	88.58